



**Chengdu Honelinks Innovation
Technology Co., Ltd.**

No.15, 1st Floor, Building 25, No.360,
Huayang Nanhu, Chengdu, China
sales@honelinks.com | Tel: +86-028-86661062
sherry@honelinks.com | Mob:+86-15196637014

OM3 patch cord

Description

Honelinks OM3 patch cord is a multimode fiber optic cable optimized for 10G/40G/100G Ethernet, with low insertion loss and high bandwidth up to 300m at 10Gbps, ideal for data centers, LANs, and high-speed networking applications.

Applications

- Data centers
- High-speed LANs
- Enterprise networks
- 40G/100G Ethernet systems
- Telecom backbones
- Server-to-server connections



Connector Table

Connector Type	Insertion Loss (dB)	Return Loss (dB)	Durability (Mating Cycles)
SC	≤ 0.3 (UPC), ≤ 0.3 (APC)	UPC ≥ 50 , APC ≥ 60	≥ 1000
LC	≤ 0.3 (UPC), ≤ 0.3 (APC)	UPC ≥ 50 , APC ≥ 60	≥ 1000
FC	≤ 0.3 (UPC), ≤ 0.3 (APC)	UPC ≥ 50 , APC ≥ 60	≥ 1000
ST	≤ 0.5 (UPC)	UPC ≥ 50	≥ 1000



Product Specifications

Feature	Simplex	Duplex	4 Fibers	8 Fibers	12 Fibers	24 Fibers	48 Fibers
Fiber Type	OM3, 50/125 μ m Multimode						
Connector	LC/SC/MPO, PC Polish						
Polarity	Type A / Type B / Type C						
Insertion Loss (Standard)	≤ 0.60 dB						
Insertion Loss (Elite)	≤ 0.35 dB						
Return Loss	≥ 20 dB (PC)						
Fiber Attenuation	850 nm ≤ 3.0 dB/km						
Jacket Material	LSZH / TPU						
Cable OD	2.0 mm/3.0mm	3.0 mm*2	6.5 mm	7.5 mm	9.5 mm	14.5 mm	18.5 mm
Operating Temperature	$-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$						
Storage Temperature	$-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$						
Durability	≥ 500 mating cycles						
Lengths	1m / 2m / 3m / 5m / 10m / Customized						
Jacket Color	Aqua						